

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

2J 5G Screw Mount Antenna, 2J7A84BGFc, Black, SMA Male, 300cm

SKU
ANT-2J-00043
MPN
SI311102920

Description

The 2J 5G Screw Mount Antenna (2J7A84BGFc), identified by SKU: ANT-2J-00043, is a versatile antenna solution designed for demanding environments. Constructed from durable ASA plastic, it boasts an IP67 rating, ensuring protection against dust and water, and operates reliably within a temperature range of -40 °C to 85 °C. This antenna features five input ports for 4x4 MIMO capabilities, providing robust connectivity across a wide frequency range from 617 MHz to 5925 MHz, with a consistent 50 Ω impedance and support for up to 35 W input power.

The antenna's linear polarisation and 360° azimuth beamwidth enhance its performance, making it ideal for applications in automotive, M2M, and base stations. Additionally, its integrated GNSS functionality supports GPS, GLONASS, QZSS, and Galileo systems, featuring an active GNSS module with a 24 dBic gain LNA, maintaining low noise for accurate positioning.

With SMA Male connectors and 3000 mm cables...

[Read More](#)





[2J](#)

2J is a worldwide supplier of antenna solutions for Automotive, Marine, Telematic, Automation and M2M markets. 2J utilise a plethora of modern engineering tools, from network analysers and anechoic chambers, to simulation software and 3D printers. These tools help reduce design phases, and enable us to react to customers' needs promptly and efficiently.

Over the past decade, 2J has established ...

RF Specification

Cables 1-4: 5GNR

Start Frequency

617 MHz

Stop Frequency

5925 MHz

Max. Input Power

35 W

Polarisation

[Linear](#)

Input Impedance

50 Ω

RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
-------	--------------	------------	--------------	--------

4	SMA Male	Straight	L-195	3000 mm
---	--------------------------	--------------------------	-----------------------	---------

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	Return Loss	VSWR	Azimuth	Avg. Gain	Efficiency
617 MHz	960 MHz	0.1 dBi	> 5.4 dB	< 3.6:1	360°	-5.3 dBi	30%
1427 MHz	2690 MHz	3.9 dBi	> 12.5 dB	< 1.9:1	360°	-3.4 dBi	47%
3300 MHz	5000 MHz	3.4 dBi	> 11.4 dB	< 1.9:1	360°	-3.8 dBi	42%
5150 MHz	5925 MHz	3.9 dBi	> 12.2 dB	< 1.8:1	360°	-3.8 dBi	42%

Cable 5: GPS/GLONASS/QZSS/Galileo

Start Frequency

1575.42 MHz

Stop Frequency

1610 MHz

Input Impedance

50 Ω

Polarisation

[Right Hand Circular \(RHCP\)](#)

Low Noise Amplifier (LNA)

LNA Gain

24 dBic

Noise Figure

≤ 1.2 dB

Power Consumption

< 137.5 mW

Min. Operating Voltage

2.7 V

Max. Operating Voltage

5.5 V

RF Connectors

Ports RF Interface Body Shape Cable Series Length

1 [SMA Male](#) [Straight](#) [L-100](#) 3000 mm

Physical Specification

Subtype

[Fin / Stud / Combo](#)

Input Ports

5

MIMO

[4x4 MIMO](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature

85 °C

Dimensions

96 x 90

Ingress Protection

[IP67](#)

Materials

[ASA Plastic](#)

Mounting

[Stud / Bulkhead / Panel](#)

Compliance/Certifications

RoHS

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

