

# 2J Dual-Band WiFi Adhesive Antenna, 2410 to 5925 MHz, TNC Male, 2m

SKU: ANT-2J-00044  
MPN: SI303100991

## Description

The 2J Dual-Band WiFi Adhesive Antenna (SKU: ANT-2J-00044) offers reliable performance across 2410 to 5925 MHz, making it ideal for a wide range of wireless applications. Designed as an adhesive patch antenna, it is compact, measuring 71 x 25 x 7 mm, and constructed from durable ABS plastic. This antenna supports a 1x1 SISO configuration, featuring a TNC male connector and a 2m cable, ensuring seamless integration into various systems.

Operating efficiently in temperatures from -40 °C to 85 °C, this antenna is RoHS compliant, emphasizing its environmental safety. It features a 50 Ω impedance and can handle up to 25 W of input power, with linear polarisation for consistent signal quality. The antenna's dual-band capability provides distinct performance metrics: in the 2.4 GHz band, it achieves a peak gain of 3.4 dBi and 57% radiated efficiency; in the 5 GHz band, it offers a peak gain of 2.6 dBi with 34% efficiency.

2J, a trusted brand...

[Read More](#)



## RF Specification

Cable 1: 2.4/5.0 GHz ISM  
**2J**

2J is a worldwide supplier of antenna solutions for Automotive, Marine, Telematic, Automation and M2M markets. 2J utilise a plethora of modern engineering tools, from network analysers and anechoic chambers, to simulation software and 3D printers. These tools help reduce design phases, and enable us to react to customers' needs promptly and efficiently.

Over the past decade, 2J has established ...

Start Frequency:	2410 MHz	Polarisation:	Linear
------------------	----------	---------------	--------

Stop Frequency:	5925 MHz	Input Impedance:	50
-----------------	----------	------------------	----

Max. Input Power:	25 W
-------------------	------

#### RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
1	RP-SMA Male	Straight	L-100	3000 mm

#### Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	Return Loss	VSWR	Avg. Gain	Efficiency
2410 MHz	2490 MHz	3.4 dBi	> -18.1 dB	< 1.3:1	-2.5 dBi	57%
4920 MHz	5925 MHz	2.6 dBi	> -11.2 dB	< 1.9:1	-4.7 dBi	34%

# Physical Specification

Subtype:	Adhesive Patch	Dimensions:	71 x 25 x 7
Input Ports:	1	Materials:	ABS Plastic
MIMO:	1x1 SISO	Mounting:	Adhesive
Min. Operating Temperature:	-40 °C	Compliance/Certifications:	RoHS
Max. Operating Temperature:	85 °C		

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

