

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

ComAnt Offset Pattern Collinear Antenna, 440 to 475 MHz, 8dBi, N Female

SKU: ANT-CA-00006 MPN: CA450C2

Description

The ComAnt Offset Pattern Collinear Antenna (SKU: ANT-CA-00006) from CompleTech is designed for professional communication applications within the 440 to 475 MHz frequency range. With a peak gain of 8dBi and a VSWR of <1.5:1, it ensures reliable signal performance for UHF applications. Featuring a single N Female RF connection, it integrates seamlessly into existing systems.

Constructed from durable ABS plastic, aluminium, and beryllium copper, this antenna is built to withstand challenging environments, certified with an IP67 rating for dust and water resistance. It operates efficiently in temperatures ranging from -40 °C to 80 °C, making it suitable for diverse outdoor installations.

The antenna's vertical polarisation and wide azimuth beamwidth of 181° provide excellent coverage in various settings. Its modular design allows easy adaptation across different applications, ensuring flexibility for changing needs. CompleTech, a renowned...

Read More

CompleTech

Complete Ch

CompleTech is a Finnish-owned company group specialising in the design, manufacturing and marketing of high quality ComAnt® communications antennas for professionals since 1990.

Radome enclosed IP67 proof ComAnt® antennas are in serial production covering all the main VHF-, UHF- and SHFbands with different radiation patterns, polarizations and gains. The modularity principle makes it easy to turn ...



RF Specification

Collinear Antenna

Start Frequency:	440 MHz	Polarisation:	Vertical (V)			
Stop Frequency:	475 MHz	Input Impedance:	50			
RF Connectors						
Ports	RF Interface	Body Shape				
1	N Female	Straight				
Frequency Test Data						

Start Freq.	Stop Freq.	Peak Gain	VSWR	Azimuth	Elevation
440 MHz	475 MHz	8 dBi	< 1.5:1	181°	27°

Physical Specification

Subtype:	Collinear	Dimensions:	985	
Input Ports:	1	Ingress Protection:	IP67	
MIMO:	1x1 SISO	Materials:	ABS Plastic, Aluminium,	
Min. Operating Temperature:	-40 °C		вегушит соррег	
Max Operating Temperature	80 °C	Mounting:	Pole Clamp 35 to 60 mm	
		Weight:	1.59 kg	
		Compliance/Certifications:	RoHS	

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

