

ComAnt Offset Pattern Dipole Antenna, 440 to 475 MHz, 5dBi, N Female

SKU: ANT-CA-00008

MPN: CA450D

Description

The ComAnt Offset Pattern Dipole Antenna (SKU: ANT-CA-00008) by ComleTech is a robust solution designed for professional communication applications within the 440 to 475 MHz frequency range. Offering a peak gain of 5dBi, it ensures reliable signal performance and is housed in a durable ABS Plastic and Polyurethane enclosure. Its IP67 rating guarantees resistance to dust and water, making it suitable for harsh environments.

This antenna features a single N Female connector, facilitating seamless RF connections with $50\ \Omega$ impedance. It supports vertical polarisation, enhancing its adaptability for various transmission requirements. The antenna's meticulous design, compliant with RoHS standards, underscores ComleTech's commitment to environmental responsibility and quality, backed by ISO 9001 certification.

ComleTech's Finnish expertise since 1990 reflects in the antenna's engineering, focusing on modularity to cater to diverse VHF, UHF...

[Read More](#)

ComleTech



ComleTech is a Finnish-owned company group specialising in the design, manufacturing and marketing of high quality ComAnt® communications antennas for professionals since 1990.

Radome enclosed IP67 proof ComAnt® antennas are in serial production covering all the main VHF-, UHF- and SHF-bands with different radiation patterns, polarizations and gains. The modularity principle makes it easy to turn ...

RF Specification

Start Frequency:	135 MHz	Polarisation:	Vertical (V)
Stop Frequency:	960 MHz	Input Impedance:	50

RF Connectors

Ports	RF Interface
1	N Female

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR	Azimuth	Elevation
440 MHz	475 MHz	5 dBi	< 1.5:1	179°	74°

Physical Specification

Subtype:	Dipole	Ingress Protection:	IP67
Input Ports:	1	Materials:	ABS Plastic, Polyurethane (PUR), Beryllium Copper
MIMO:	1x1 SISO	Compliance/Certifications:	RoHS
Min. Operating Temperature:	-40 °C		
Max. Operating Temperature:	80 °C		

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

