

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

Laird Connectivity FG9026 Omni- Directional Antenna 900MHz 8dBi

SKU
ANT-LA-00001
MPN
814-FG9026

Description

The Laird Connectivity FG9026 Omni-Directional Antenna is a high-performance collinear antenna ideal for applications requiring reliable 900MHz communication. Constructed from durable fibreglass, this antenna operates efficiently within a broad temperature range of -55 °C to 85 °C, ensuring robust performance in various environmental conditions.

With a peak gain of 8dBi and vertical polarisation, the FG9026 delivers strong, consistent signals across the 902 MHz to 928 MHz frequency range. Its design supports a 360° azimuth beamwidth, making it suitable for wide-area coverage in industrial, commercial, and agricultural applications. The antenna features a single N Female RF connection, allowing seamless integration with existing systems.

Designed with a 1x1 SISO configuration, the FG9026 supports up to 100W input power, maintaining a low VSWR of <1.5:1 for optimal signal clarity. Its 50 Ω impedance ensures compatibility with a wide range...

[Read More](#)



[Laird Connectivity](#)

Laird Connectivity designs, develops, manufactures, and supports wireless systems solutions and performance materials for wireless and other advanced electronics applications. Its wireless systems solutions include infrastructure antenna systems, embedded wireless modules, telematics and wireless M2M solutions, wireless automation and control solutions, and connectivity products.

We simplify the ...

RF Specification

Start Frequency

902 MHz

Stop Frequency

928 MHz

Max. Input Power

100 W

Polarisation

[Vertical \(V\)](#)

Input Impedance

50 Ω

RF Connectors

Ports RF Interface

1 [N Female](#)

Frequency Test Data

Start Freq. Stop Freq. Peak Gain VSWR Azimuth Elevation

902 MHz 928 MHz 6 dBi < 1.5:1 360° 30°

Physical Specification

Subtype

[Collinear](#)

Input Ports

1

MIMO

[1x1 SISO](#)

Min. Operating Temperature

-55 °C

Max. Operating Temperature

85 °C

Dimensions

1549.4 x 33.27

Materials

[Fibreglass \(GRP\)](#)

Weight

0.5 kg

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to

change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

