Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

Laird YA9-11 11 dBi Yagi Antenna, 860 to 960MHz

SKU
ANT-LA-00002
MPN
814-YA9-11

Description

The Laird YA9-11 Yagi Antenna, designed by Laird Connectivity, offers exceptional performance for wireless systems within the 860 to 960 MHz frequency range. With an 11 dBi peak gain, this antenna provides robust signal strength, ideal for applications requiring reliable long-range communication. Constructed from durable Stainless Steel (304), it ensures resilience in diverse environmental conditions, operating effectively from -45°C to 70°C.

The antenna is vertically polarised and features a single N Female RF connection, supporting up to 100 W of input power with a 50 Ω impedance, making it suitable for various industrial and commercial applications. Its compact design, measuring 35.4 inches in length and weighing only 1.1 kg, facilitates easy installation and integration into existing systems.

Compliant with RoHS standards, the YA9-11 Yagi Antenna is a dependable choice for infrastructure antenna systems, telematics, wireless M2M...

Read More

Laird Connectivity

Laird Connectivity designs, develops, manufactures, and supports wireless systems solutions and performance materials for wireless and other advanced electronics applications. Its wireless systems solutions include infrastructure antenna systems, embedded wireless modules, telematics and wireless M2M solutions, wireless automation and control solutions, and connectivity products.

We simplify the ...

RF Specification

Start Frequency

860 MHz
Stop Frequency
960 MHz
Max. Input Power
100 W
Polarisation
Vertical (V)
Input Impedance
50 Ω
RF Connectors

Ports	RF Interface
1	N Female

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR	Azimuth	F/B Ratio
860 MHz	960 MHz	11 dBi	< 1.5:1	50°	> 15 dB

Physical Specification

Subtype
Yagi
Input Ports
1
MIMO
1x1 SISO
Min. Operating Temperature
-45 °C
Max. Operating Temperature
70 °C
Dimensions
35.4 in x 6 in
Materials
Stainless Steel (304)
Weight
1.1 kg
Compliance/Certifications
RoHS

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility

therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

