

# Peplink Mobility 02 (Puma 020-R-B-6), 2xWiFi, 2400-6000MHz, IP68, RP-SMA, White, 6.5 ft / 2.0m

SKU: ANT-MB-02-R-W-6

MPN: PUMA-020-R-B-6

## Description

The Peplink Mobility 02, also known as the Puma 020-R-B-6, is a robust dual-band WiFi antenna designed to enhance wireless connectivity across a broad range of environments. Operating within the 2400-6000 MHz frequency range, it supports 2x2 MIMO technology, making it ideal for applications requiring stable and high-speed internet access, such as in mobile, industrial, and outdoor settings. Its IP68 rating ensures it is dust-tight and protected against prolonged submersion, making it highly durable and suitable for harsh weather conditions.

Crafted from ABS plastic, this antenna is built to withstand extreme temperatures, ranging from -40°C to 80°C, ensuring reliable performance in diverse climates. The Peplink Mobility 02 features RP-SMA connectors and is designed for easy integration with existing systems, offering a maximum input power of 10 W and a linear polarisation for optimal signal reception. Its compact dimensions make it a...

[Read More](#)



## Peplink

Peplink makes connectivity reliable. Peplink's ecosystem, SpeedFusion technology and SD-WAN routers have been deployed around the world, helping thousands of customers from many industries increase bandwidth, enhance Internet reliability, reduce connectivity cost, or enable new deployment possibilities.

Founded by Alex Chan in Hong Kong in 2006, today Peplink is based in Mountain View, California.

# RF Specification

## WiFi

Start Frequency:	2400 MHz	Polarisation:	Linear
Stop Frequency:	6000 MHz	Input Impedance:	50
Max. Input Power:	10 W		

## RF Connectors

Ports	RF Interface	Body Shape	Length
1	RP-SMA Male	Straight	2000 mm
1	RP-SMA Male	Straight	2000 mm

## Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR
2400 MHz	2500 MHz	6.2 dBi	< 2:1
4900 MHz	6000 MHz	7.3 dBi	< 2:1

# Physical Specification

Subtype:	Fin / Stud / Combo	Dimensions:	1.42 in. / 36mm x 5.12 in. / 130mm
Input Ports:	2	Ingress Protection:	IP68
MIMO:	2x2 MIMO	Materials:	ABS Plastic
Min. Operating Temperature:	-40 °C	Compliance/Certifications:	RoHS
Max. Operating Temperature:	80 °C		

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

