

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

Peplink Mobility 42G (Puma 421), 7-in-15G ready, 4 LTE, 2 Wifi, 1 GPS, OP68, QMA, White, 0.3M

SKU: ANT-MB-42G-Q-W-1 MPN: ANT-MB-42G-Q-W-1

Description

The Peplink Mobility 42G (Puma 421) is a versatile 7-in-1 antenna system designed for robust wireless connectivity in demanding environments. It is 5G-ready and features four LTE, two Wi-Fi, and one GPS input, making it ideal for various applications such as public safety, transportation, and mobile healthcare. With its 4x4 MIMO configuration, the antenna ensures enhanced data throughput and reliable connectivity. The wide frequency range from 617 MHz to 6000 MHz supports both LTE and 5G networks, enabling seamless communication in diverse conditions.

The antenna's durable construction, featuring IP68-rated polycarbonate housing, provides excellent protection against dust and water, making it suitable for outdoor and harsh environments. It operates effectively within a temperature range of -40 °C to 80 °C, ensuring performance stability in extreme weather conditions. The GPS component offers accurate positioning with a right-hand...

Read More





Peplink

Peplink makes connectivity reliable. Peplink's ecosystem, SpeedFusion technology and SD-WAN routers have been deployed around the world, helping thousands of customers from many industries increase bandwidth, enhance Internet reliability, reduce connectivity cost, or enable new deployment possibilities.

Founded by Alex Chan in Hong Kong in 2006, today Peplink is based in Mountain View, California.

RF Specification

Cellular

Start Frequency:	617 MHz	Polarisation:	Linear
Stop Frequency:	6000 MHz	Input Impedance:	50
Max. Input Power:	10 W		

RF Connectors

Ports	RF Interface	Body Shape	Length
1	QMA Male	Straight	300 mm

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR
617 MHz	960 MHz	4.4 dBi	< 2.5:1
1710 MHz	2700 MHz	7.8 dBi	< 2.5:1
3400 MHz	4200 MHz	7.9 dBi	< 2.5:1
5000 MHz	6000 MHz	8.2 dBi	< 2.5:1

Wi-Fi

Start Frequency:	2400 MHz	Polarisation:	Linear
Stop Frequency:	6000 MHz	Input Impedance:	50
Max. Input Power:	10 W		

RF Connectors

Ports	RF Interface	Body Shape	Length
1	QMA Male	Straight	300 mm

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR
2400 MHz	2500 MHz	5 dBi	< 2.5:1
5000 MHz	6000 MHz	7.5 dBi	< 2.5:1

GPS

Start Frequency:	1561 MHz	Input Impedance:	50
Stop Frequency:	1602 MHz	Polarisation:	Right Hand Circular (RHCP)

Low Noise Amplifier (LNA)

LNA Gain:	28 dBic	Min. Operating Voltage:	3.3 V
Noise Figure:	≤ 1.5 dB	Max. Operating Voltage:	3.3 V
Power Consumption:	< 8.5 mW		

RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
1	QMA Male	Straight	RG-174	300 mm

Physical Specification

Subtype:	Fin / Stud / Combo	Dimensions:	58 x 208 (H x Dia)
Input Ports:	7	Ingress Protection:	IP68
MIMO:	4x4 MIMO	Materials:	Polycarbonate (PC)
Min. Operating Temperature:	-40 °C	Compliance/Certifications:	RoHS
Max. Operating Temperature:	80 °C	Mechanical Compliance:	IEC 60529: IP Code
		MIL-STD-810: Environmental Du	, urability

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

