Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

Peplink Mobility 42G (Puma 421), 7-in-1 5G ready, 4 LTE, 2 Wifi, 1 GPS, OP68, QMA, White, 0.3M

SKU
ANT-MB-42G-Q-W-1
MPN
ANT-MB-42G-Q-W-1

Description

The Peplink Mobility 42G (Puma 421) is a versatile 7-in-1 antenna system designed for robust wireless connectivity in demanding environments. It is 5G-ready and features four LTE, two Wi-Fi, and one GPS input, making it ideal for various applications such as public safety, transportation, and mobile healthcare. With its 4x4 MIMO configuration, the antenna ensures enhanced data throughput and reliable connectivity. The wide frequency range from 617 MHz to 6000 MHz supports both LTE and 5G networks, enabling seamless communication in diverse conditions.

The antenna's durable construction, featuring IP68-rated polycarbonate housing, provides excellent protection against dust and water, making it suitable for outdoor and harsh environments. It operates effectively within a temperature range of -40 °C to 80 °C, ensuring performance stability in extreme weather conditions. The GPS component offers accurate positioning with a right-hand...

Read More



Peplink

Peplink makes connectivity reliable. Peplink’s ecosystem, SpeedFusion technology and SD-WAN routers have been deployed around the world, helping thousands of customers from many industries increase bandwidth, enhance Internet reliability, reduce connectivity cost, or enable new deployment possibilities.

Founded by Alex Chan in Hong Kong in 2006, today Peplink is based in Mountain View, California.

RF Specification

Cellular

Start Frequency
617 MHz
Stop Frequency
6000 MHz
Max. Input Power
10 W
Polarisation
Linear
Input Impedance
50 Ω
RF Connectors

Ports	RF Interface	Body Shape	Length
1	QMA Male	Straight	300 mm

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR

617 MHz	960 MHz	4.4 dBi	< 2.5:1
1710 MHz	2700 MHz	7.8 dBi	< 2.5:1
3400 MHz	4200 MHz	7.9 dBi	< 2.5:1
5000 MHz	6000 MHz	8.2 dBi	< 2.5:1

Wi-Fi

Start Frequency
2400 MHz
Stop Frequency
6000 MHz
Max. Input Power
10 W
Polarisation
Linear
Input Impedance
50 Ω
RF Connectors

Ports	RF Interface	Body Shape	Length
1	QMA Male	Straight	300 mm

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR
2400 MHz	2500 MHz	5 dBi	< 2.5:1
5000 MHz	6000 MHz	7.5 dBi	< 2.5:1

GPS

Start Frequency
1561 MHz
Stop Frequency
1602 MHz
Input Impedance
50 Ω
Polarisation
Right Hand Circular (RHCP)

Low Noise Amplifier (LNA)

LNA Gain

28 dBic
Noise Figure
≤ 1.5 dB
Power Consumption
< 8.5 mW
Min. Operating Voltage
3.3 V
Max. Operating Voltage
3.3 V
RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
1	QMA Male	Straight	RG-174	300 mm

Physical Specification

Subtype
Fin / Stud / Combo
Input Ports
7
MIMO
4x4 MIMO
Min. Operating Temperature
-40 °C
Max. Operating Temperature
80 °C
Dimensions
58 x 208 (H x Dia)
Ingress Protection
IP68
Materials
Polycarbonate (PC)
Compliance/Certifications
RoHS
Mechanical Compliance
IEC 60529: IP Code
,
MIL-STD-810: Environmental Durability

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility

therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

