

Peplink Mobility 42G (Puma 421-S-W-6), 7-in-1 5G Ready cellular, 4xLTE, 2 x Wifi, 1xGPS, White, 2m cable, SMA

SKU: ANT-MB-42G-S-W-6

MPN: ANT-MB-42G-S-W-6

Description

The Peplink Mobility 42G (Puma 421-S-W-6) is a versatile 7-in-1 antenna system designed for seamless connectivity across multiple networks. It is specifically crafted to enhance mobile communications with its 5G readiness, making it highly suitable for demanding environments such as public safety, mobile healthcare, and transportation. The antenna supports 4x LTE, 2x Wi-Fi, and 1x GPS, ensuring robust and reliable connections. Its 4x4 MIMO capability provides high-speed data transfer, essential for applications requiring uninterrupted connectivity. The inclusion of dual-band Wi-Fi (2.4GHz and 5GHz) allows for flexible deployment in various wireless environments.

The Mobility 42G operates efficiently over a wide frequency range from 617 MHz to 6000 MHz, offering peak gains that significantly improve signal reception and transmission. With an ingress protection rating of IP68, it is well-suited for outdoor use, resisting harsh...

[Read More](#)



Peplink

Peplink makes connectivity reliable. Peplink's ecosystem, SpeedFusion technology and SD-WAN routers have been deployed around the world, helping thousands of customers from many industries increase bandwidth, enhance Internet reliability, reduce connectivity cost, or enable new deployment possibilities.

Founded by Alex Chan in Hong Kong in 2006, today Peplink is based in Mountain View, California.

RF Specification

Cellular

Start Frequency:	617 MHz	Polarisation:	Linear
Stop Frequency:	6000 MHz	Input Impedance:	50
Max. Input Power:	10 W		

RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
1	SMA Male	Straight	L-200	2000 mm
1	SMA Male	Straight	L-200	2000 mm
1	SMA Male	Straight	L-200	2000 mm
1	SMA Male	Straight	L-200	2000 mm

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR
617 MHz	960 MHz	4.4 dBi	< 2.5:1
1710 MHz	2700 MHz	7.8 dBi	< 2.5:1
3400 MHz	4200 MHz	7.9 dBi	< 2.5:1
5000 MHz	6000 MHz	8.2 dBi	< 2.5:1

Wi-Fi

Start Frequency:	2400 MHz	Polarisation:	Linear
Stop Frequency:	6000 MHz	Input Impedance:	50
Max. Input Power:	10 W		

RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
1	RP-SMA Male	Straight	L-200	2000 mm
1	RP-SMA Male	Straight	L-200	2000 mm

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR
2400 MHz	2500 MHz	5 dBi	< 2.5:1
5000 MHz	6000 MHz	7.5 dBi	< 2.5:1

GPS

Start Frequency:	1561 MHz	Input Impedance:	50
Stop Frequency:	1602 MHz		

Low Noise Amplifier (LNA)

LNA Gain:	28 dBic	Min. Operating Voltage:	3.3 V
Noise Figure:	≤ 1.5 dB	Max. Operating Voltage:	3.3 V
Power Consumption:	< 8.5 mW		

RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
1	SMA Male	Straight	L-200	2000 mm

Physical Specification

Subtype:	Fin / Stud / Combo	Dimensions:	58 x 208 (H x Dia)
Input Ports:	7	Ingress Protection:	IP68
MIMO:	4x4 MIMO	Materials:	Polycarbonate (PC)
Min. Operating Temperature:	-40 °C	Compliance/Certifications:	RoHS
Max. Operating Temperature:	80 °C	Mechanical Compliance:	MIL-STD-810: Environmental Durability

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

