

Peplink Mobility 82G, 8xLTE/5G, 2 x WiFi, 1xGPS, 600-6000MHz, IP67, SMA, Black, 6.5ft / 2m

SKU: ANT-MB-82G-S-B-6
 MPN: ANT-MB-82G-S-B-6

Description

The Peplink Mobility 82G is a robust multi-band antenna designed for high-performance connectivity in challenging environments. Supporting 8x LTE/5G MIMO, it enhances cellular signal reception, making it ideal for mobile or remote applications requiring reliable internet access. With a broad frequency range of 600-6000 MHz, it ensures compatibility with various network providers and technologies, including emerging 5G networks. The antenna integrates two WiFi inputs and a GPS module, providing comprehensive wireless and location capabilities for vehicles, maritime, or industrial setups.


Constructed from durable polycarbonate, the Mobility 82G is built to withstand harsh conditions, as evidenced by its IP67 rating and compliance with MIL-STD-810 for environmental durability. This makes it suitable for outdoor installations where exposure to dust and water is a concern. The 8x8 MIMO configuration maximises data throughput and connection...

[Read More](#)



RF Specification

Cellular

	Peplink		
	Start Frequency: 617 MHz	Polarisation: Linear	
Stop Frequency: 6000 MHz	Peplink makes connectivity reliable. Peplink's ecosystem, SpeedFusion technology and SD-WAN routers have been deployed around the world, helping thousands of customers from many industries increase bandwidth, enhance Internet reliability, reduce connectivity cost, or enable new deployment possibilities.	Input Impedance: 50	
Max. Input Power: 10 W	Founded by Alex Chan in Hong Kong in 2006, today Peplink is based in Mountain View, California.		

RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
1	SMA Male	Straight	RG-58	1981.2 mm

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR	Azimuth
617 MHz	960 MHz	5.4 dBi	< 2:1	360°
1400 MHz	2700 MHz	7.5 dBi	< 2:1	360°
3400 MHz	4200 MHz	8.1 dBi	< 2:1	360°
5000 MHz	6000 MHz	8.7 dBi	< 2:1	360°

WiFi

Start Frequency:	2400 MHz	Polarisation:	Linear
Stop Frequency:	6000 MHz	Input Impedance:	50
Max. Input Power:	10 W		

RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
1	RP-SMA Male	Straight	RG-58	1981.2 mm

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR	Azimuth
2400 MHz	2500 MHz	6 dBi	< 2:1	360°
5000 MHz	6000 MHz	7.4 dBi	< 2:1	360°

GPS

Start Frequency:	1575 MHz	Input Impedance:	50
Stop Frequency:	1602 MHz	Polarisation:	Right Hand Circular (RHCP)

Low Noise Amplifier (LNA)

LNA Gain:	29 dBic	Max. Operating Voltage:	3.3 V
Power Consumption:	< 6 mW		

RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
1	SMA Male	Straight	RG-174	1981.2 mm

Physical Specification

Subtype:	Fin / Stud / Combo	Dimensions:	62.5 x 427.4 (H x Dia)
Input Ports:	3	Ingress Protection:	IP67
MIMO:	8x8 MIMO	Materials:	Polycarbonate (PC)
Min. Operating Temperature:	-40 °C	Compliance/Certifications:	RoHS
Max. Operating Temperature:	80 °C	Mechanical Compliance:	MIL-STD-810: Environmental Durability

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

