

# Panorama Low Profile Antenna, 617 to 6000 MHz, 2m SMA Male

SKU: ANT-PA-00011

MPN: LPBEM-6-60-2SP

## Description

The Panorama Low Profile Antenna (SKU: ANT-PA-00011), model LPBEM-6-60-2SP, offers exceptional coverage across a wide frequency range of 617 MHz to 6000 MHz. Designed by Panorama Antennas, this monopole antenna is ideal for demanding environments, thanks to its robust ASA plastic and aluminium construction, and IPX6 ingress protection rating. Its compact dimensions of 96 x 48 mm make it easy to integrate into various setups.

This vertical polarised antenna is engineered for superior RF performance, with peak gain values reaching up to 8.0 dBi. It maintains a consistent VSWR of less than 2.5:1 across all specified frequency bands, ensuring minimal signal reflection and optimal efficiency. The antenna supports a 50 Ω impedance and can handle up to 25 W of input power, making it suitable for high-performance applications.

Equipped with a 2m SMA Male connection via RG-174 cable, it ensures reliable connectivity. Its operating temperature...

[Read More](#)



## Panorama Antennas

Panorama's constant cutting-edge research ensures that our antennas meet the demands of the very latest communication technologies. Trusted by thousands of professionals and consumers the world over, our antennas are depended upon to provide communications even in the most challenging conditions.

Currently, Panorama specialises in professional antenna solutions for modern communications ...

# RF Specification

Start Frequency:	617 MHz	Polarisation:	Vertical (V)
Stop Frequency:	6000 MHz	Input Impedance:	50
Max. Input Power:	25 W		

## RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
1	SMA Male	Straight	RG-174	2000 mm

## Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR
617 MHz	960 MHz	3 dBi	< 2.5:1
1710 MHz	2170 MHz	4 dBi	< 2.5:1
2170 MHz	2700 MHz	5 dBi	< 2.5:1
3400 MHz	3800 MHz	6 dBi	< 2.5:1
4000 MHz	6000 MHz	8 dBi	< 2.5:1

# Physical Specification

Subtype:	Monopole	Dimensions:	96 x 48 (H x Dia)
Input Ports:	1	Ingress Protection:	IPX6
MIMO:	1x1 SISO	Materials:	ASA Plastic, Aluminium
Min. Operating Temperature:	-40 °C		
Max. Operating Temperature:	80 °C		

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

