

C-10-CPUSE-43-A16

10 dB, Low PIM Air Directional Coupler, 555–2700 MHz



OBSOLETE

This product was discontinued on: **October 31, 2019**

Replaced By:

C-10-UW-43-A16

10 dB, Air Directional Coupler, 555–6000 MHz

Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

Product Type

Directional coupler

General Specifications

Device Type

Coupler

Application

Indoor/Outdoor

Color

Silver

Inner Contact Plating

Silver

Interface

4.3-10 Female

Outer Contact Plating

Trimetal

Dimensions

Height

22 mm | 0.866 in

Width

75 mm | 2.953 in

Length

158 mm | 6.22 in

Electrical Specifications

3rd Order IMD

-162 dBc

3rd Order IMD Test Method

Two +43 dBm carriers

C-10-CPUSE-43-A16

Insertion Loss at Frequency Band	0.7 dB @ 555–2700 MHz
Return Loss, minimum	20.8 dB
Average Power, maximum	300 W
Coupling	10 dB
Coupling Tolerance	±1.0dB @ 575–2700 MHz ±1.5dB @ 555–575 MHz
Impedance	50 ohm
Isolation at Frequency Band	30 dB @ 555–2700 MHz
Operating Frequency Band	555 – 2700 MHz
Peak Power, maximum	1 kW
Reflected Power, maximum	100 W
VSWR	1.2

Mechanical Specifications

Coupling Nut Proof Torque	7 N-m 61.955 in lb
----------------------------------	----------------------

Environmental Specifications

Operating Temperature	-35 °C to +85 °C (-31 °F to +185 °F)
Relative Humidity	Up to 100%
Ingress Protection Test Method	IEC 60529:2001, IP65

Packaging and Weights

Height, packed	45 mm 1.772 in
Width, packed	75 mm 2.953 in
Length, packed	180 mm 7.087 in
Weight, gross	0.43 kg 0.948 lb
Weight, net	0.37 kg 0.816 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant

C-10-CPUSE-43-A16

