

F4A-PDFDR-3M5

FSJ4-50B SureFlex® Jumper with interface types 7-16 DIN Female and 7-16 DIN Male Right Angle, 3.5 m



Product Classification

Product Type	SureFlex® standard
Product Series	FSJ4-50B

General Specifications

Body Style, Connector A	Straight
Body Style, Connector B	Right angle
Interface, Connector A	7-16 DIN Female
Interface, Connector B	7-16 DIN Male
Specification Sheet Revision Level	A

Dimensions

Length	3.5 m 11.483 ft
Nominal Size	1/2 in

Electrical Specifications

DTF, Connector A	-32 dB
DTF, Connector B	-32 dB

VSWR/Return Loss

Frequency Band	VSWR, typical	Return Loss, typical (dB)
0–3000 MHz	1.106	25.96
2.2–2.7 GHz	1.083	27.99

Jumper Assembly Sample Label

F4A-PDFDR-3M5



Environmental Specifications

Immersion Test Method Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system



Included Products

- | | |
|---------|--|
| F4DR-C | - 7-16 DIN Male Right Angle for 1/2 in FSJ4-50B cable |
| F4NR-HC | - Type N Male Right Angle for 1/2 in FSJ4-50B cable |
| L4DR-PS | - 7-16 DIN Male Right Angle Positive Stop™ for 1/2 in LDF4-50A cable |
| L4NR-PS | - Type N Male Right Angle Positive Stop™ for 1/2 in LDF4-50A cable |